

Secrétariat général de la défense et de la sécurité nationale

Agence nationale de la sécurité des systèmes d'information

Certification Report ANSSI-CC-2016/47

ID-One eIDL v1.0 in EAC configuration with BAP and AA on P60x080PVC/PVG components

Paris, 12 july 2016

Courtesy Translation



Warning

This report is designed to provide sponsors with a document enabling them to assess the security level of a product under the conditions of use and operation defined in this report for the evaluated version. It is also designed to provide the potential purchaser of the product with the conditions under which he may operate or use the product so as to meet the conditions of use for which the product has been evaluated and certified; that is why this certification report must be read alongside the evaluated user and administration guidance, as well as with the product security target, which presents threats, environmental assumptions and the supposed conditions of use so that the user can judge for himself whether the product meets his needs in terms of security objectives.

Certification does not, however, constitute a recommendation product from ANSSI (French Network and Information Security Agency), and does not guarantee that the certified product is totally free of all exploitable vulnerabilities.

Any correspondence about this report has to be addressed to:

Secrétariat général de la défense et de la sécurité nationale Agence nationale de la sécurité des systèmes d'information Centre de certification 51, boulevard de la Tour Maubourg 75700 PARIS cedex 07 SP France

certification.anssi@ssi.gouv.fr

Reproduction of this document without any change or cut is authorised.

Certification report reference					
ANSSI-CC-2016/47					
Product name					
ID-One eIDL v1.0 in EAC configuration with BAP and AA on					
P60x080PVC/P	VG components				
Product reference					
SAAAAR 080031 : ePass	s V3 Full EACv2 on NXP				
SAAAAR 082456 :	Code r6.0 Generic				
SAAAAR 082844 : Optional Co	ode r4.0 Digital Blurred Image				
Protection profile conformity					
No	ne				
Evaluation criteria and version					
Common Criteria v	ersion 3.1 revision 4				
Evaluation level					
EAL 5 au	igmented				
ALC_DVS.2,					
Developers					
Oberthur Technologies	NXP Semiconductors				
420 rue d'Estienne d'Orves	Box 54 02 40,				
CS 40008	Dox 54 02 40, D-22502 Hamburg, Allemagne				
92705 Colombes, France	,,, _,, _				
Sponsor					
Oberthur T	echnologies				
	U				
420 rue d'Estienne d'Orves					
CS 40008 92705 Colombes, France					
Evaluation facility	ides, France				
	Т БТТ				
CEA - LETI					
17 rue des martyrs, 38054 Recognition arrangements	Grenoble Cedex 9, France				
	SOC IS				
CCRA	SOG-IS				
	Same an reason of the second				
	Contrast Section				
The product is recognised at EAL2 level.					

Introduction

The Certification

Security certification for information technology products and systems is governed by decree number 2002-535 dated April, 18th 2002, modified. This decree stipulates that:

- The French Network and Information Security Agency draws up **certification reports**. These reports indicate the features of the proposed security targets. They may include any warnings that the authors feel the need to mention for security reasons. They may or may not be transmitted to third parties or made public, as the sponsors desire (article 7).
- The **certificates** issued by the Prime Minister certify that the copies of the products or systems submitted for evaluation fulfil the specified security features. They also certify that the evaluations have been carried out in compliance with applicable rules and standards, with the required degrees of skill and impartiality (article 8).

The procedures are available on the Internet site <u>www.ssi.gouv.fr</u>.

Contents

1. THE PRODUCT	
1.1. PRESENTATION OF THE PRODUCT	6
1.2. EVALUATED PRODUCT DESCRIPTION	6
1.2.1. Introduction	
1.2.2. Product identification	
1.2.3. Security services	
1.2.4. Architecture	
1.2.5. Life cycle	
1.2.6. Evaluated configuration	
2. THE EVALUATION	
2.1. EVALUATION REFERENTIAL	0
2.1. EVALUATION REFERENTIAL	
2.2. EVALUATION WORK 2.3. CRYPTOGRAPHIC MECHANISMS ROBUSTNESS ANALYSIS ACCORDIN	,
TECHNICAL STANDARDS	
2.4. RANDOM NUMBER GENERATOR ANALYSIS	
	11
3. CERTIFICATION	
3.1. CONCLUSION	
3.2. RESTRICTIONS	
3.3. RECOGNITION OF THE CERTIFICATE	
3.3.1. European recognition (SOG-IS)	
3.3.2. International common criteria recognition (CCRA)	
ANNEX 1. EVALUATION LEVEL OF THE PRODUCT	
ANNEX 2. EVALUATED PRODUCT REFERENCES	
ANNEX 3. CERTIFICATION REFERENCES	

1. The product

1.1. Presentation of the product

The evaluated product is the smart card « ID-One eIDL v1.0 in EAC configuration with BAP and AA on P60x080PVC/PVG components », which can be in contact or contactless mode. This product is developed by *OBERTHUR TECHNLOGIES* on a component manufactured by *NXP SEMICONDUCTORS*.

This product implements electronic driving license functionalities. This product is used to verify a driving license's authenticity through an inspection system.

The evaluation target is composed of the ID-One eIDL v1.0 application, in EAC (*Extended Access Control*) configuration with BAP (*Basic Access Protection*) and AA (*Active Authentication*), which carries out the electronic driving license functions.

This micro-controller and its embedded software can be integrated into modules or *inlays*. The final product can be a driving license, plastic card, etc.

1.2. Evaluated product description

1.2.1. Introduction

The security target [ST] defines the evaluated product, its evaluated security functionalities and its operational environment.

1.2.2. Product identification

The configuration list [CONF] identifies the product's constituent elements.

The certified version of the product can be identified by the following elements:

- Commercial name: ID-One eIDL v1.0;
- SAAAAR¹ code of ROM code : 080031;
- Mandatory patch code: 412E4D1EC087005B56A9A2CAC0B6558F4CAA E041D8B5A69345559B562A6F4C8E;
- Optional patch code : E339C30BC6A81162413612FE2698284FA6CD28AA5 CF5257A20B83611E58E9BEE;
- Component code (on 42 bytes): XXXXvvvvXX..XX where vvvv can take the following values:
 - '6C14' for P60D080PVC component;
 - '6014' for P60D080PVG component;
 - '6019' for P60C080PVG component.

It can be decided whether or not to load the optional patch and whether or not to the *Digital Blurred Image* function.

¹ S: site code (0 for France), AAAA: article based on 4 numbers, R: software *release* or version.

The "SAAAAR and patch" codes can be verified using a GetData command with the DF66 tag. The component code can be verified using a GetData command with the 9F7F tag described in the [GUIDES].

1.2.3. Security services

The main security services provided by the product are:

- Integrity Protection of the cardholder's data stored in the card;
- Access control to the cardholder's data stored in the card;
- Integrity and confidentiality protection, through the *Secure Messaging* mechanism, of the data read on the card;
- Verification of the certificates' validation chain;
- Authentication of the micro-controller using the optional « *Active Authentication* » mechanisms;
- Strong mutual authentication between the micro-controller and the inspection system by the EAC (*« Extended Access Control »*) mechanism prior to any access to biometric data.

There is an optional non evaluated function of *Digital Blurred Image* which makes the photo illegible in case of a fraudulent use.

1.2.4. Architecture

The product is a closed smart card which contained the following components:

- a micro-controller P60x080PVC/PVG manufactured by *NXP Semiconductors*, in P60D080PVC, P60D080PVG or P60C080PVG configuration;
- the "BIOS" software giving access to micro-controller functionalities;
- a dedicated cryptographic library;
- the *Perso* personalization application;
- a LDS¹ application supporting EAC, PACE, PACE CAM, CA, AA and BAP mechanisms;
- The eID application;
- The *eSign* application outside of the evaluation scope;
- The *Dauth* application outside of the evaluation scope.

¹Logical Data Structure.

1.2.5. Life cycle

The product's life cycle is organised as follow:

	Phase	Actor	Covered by					
Step 1	Development	Oberthur	ALC					
		TECHNOLOGIES						
Step 2	Development	NXP	Component					
		Semiconductors	Certification					
Step 3	Manufacturing	NXP	Component					
		Semiconductors	Certification					
	TOE delivery point							
Step 4	IDL manufacturer	IDL manufacturer	AGD_PRE					
	(Pre-perso)							
Step 5	IDL manufacturer	IDL manufacturer	AGD_PRE					
	(Pre-perso)							
Step 6	Personalization	Personalization agent	AGD_PRE					
Step 7	Operational use	End user	AGD_OPE					

The product has been developed on the following site:

OBERTHUR TECHNOLOGIES – Colombes site

420 rue d'Estienne d'Orves 92700 Colombes France

OBERTHUR TECHNOLOGIES – Pessac site

Parc Scientifique UNITEC 1 4 allée du Doyen Georges Brus – Porte 2 33600 Pessac France

The micro-controller is developed and manufactured by *NXP SEMICONDUCTORS*. The development and manufacturing sites for the micro-controller are detailed in the certification report under the reference [BSI-DSZ-CC-0837-V2-2014].

The "product administrators" are the nations or authorities issuing the driving license. The "product users" are both the holders of driving license and the inspection systems during the use phase.

1.2.6. Evaluated configuration

The product is a closed card that can be personalized into different configurations. This certification report applies to the configuration including the following mechanisms:

- Extended Access Control;
- Active Authentication;
- Basic Access Protection.

2. The evaluation

2.1. Evaluation referential

The evaluation has been performed in compliance with the **Common Criteria version 3.1 revision 4** [CC], in accordance with the Common Evaluation Methodology defined in [CEM].

For assurance components which are not covered by the [CEM] manual, methods specific to the evaluation facility were used.

In order to meet specific features of smart cards, the [JIWG IC] and [JIWG AP] guides were applied. Thus, the AVA_VAN level was determined using the rating scale of the [JIWG AP] guide. For the record, this rating scale is more demanding than the one defined by default in the standard method [CC], used for other categories of products (software products for example).

2.2. Evaluation work

The evaluation has been performed according to the composition scheme defined in the guide [COMP], in order to assess that no weakness arises from the integration of the software in the certified microcontroller.

Therefore, the results of the evaluation of the microcontroller « P60x080PVC/PVG » at EAL6 level augmented with ALC_FLR.1 and ASE_TSS.2 components, compliant with the [BSI-PP-0035-2007] protection profile, have been used. This microcontroller has been certified the 24th October 2014 under the reference [BSI-DSZ-CC-0837-V2-2014].

The evaluation technical report [ETR], delivered to ANSSI the 6th July 2016, provides details on the work performed by the evaluation facility and assesses that all evaluation tasks are "**pass**".

2.3. Cryptographic mechanisms robustness analysis according to the ANSSI's technical standards

The rating of the cryptographic mechanisms robustness, according to the ANSSI [REF] technical standards, was not carried out. However, the evaluation has not allowed to highlight design and construction vulnerability for the intended target namely AVA_VAN.5 level.

2.4. Random number generator analysis

The physical random number generator used by the final product was evaluated within the scope of the micro-controller evaluation (Refer to [BSI-DSZ-CC-0837-V2-2014]).

In addition, as required in the ANSSI cryptographic standard ([REF]), the output of the physical random number generator is reprocessed using a cryptographic function.

The results were taken into account in the independent vulnerability analysis carried out by the evaluator and found no evidence of exploitable vulnerability for the AVA_VAN.5 level targeted.

3. Certification

3.1. Conclusion

The evaluation was carried out according to the current rules and standards, with the required competency and impartiality of a licensed evaluation facility. All the work performed permits the release of a certificate in conformance with the decree 2002-535.

This certificate testifies that the product « ID-One eIDL v1.0 in EAC configuration with BAP and AA on P60x080PVC/PVG components » submitted for evaluation fulfils the security features specified in its security target [ST] for the evaluation level EAL5 augmented by ALC_DVS.2 and AVA_VAN.5 components.

3.2. Restrictions

This certificate only applies on the product specified in chapter 1 of this certification report.

The user of the certified product shall respect the security objectives for the operational environment, as specified in the security target [ST], and shall respect the recommendations in the guidance [GUIDES].

3.3. Recognition of the certificate

3.3.1. European recognition (SOG-IS)

This certificate is released in accordance with the provisions of the SOG-IS agreement [SOG-IS].

The European Recognition Agreement made by SOG-IS in 2010 allows recognition from Signatory States of the agreement¹, of ITSEC and Common Criteria certificates. The European recognition is applicable, for smart cards and similar devices, up to ITSEC E6 High and CC EAL7 levels. The certificates that are recognized in the agreement scope are released with the following marking:



3.3.2. International common criteria recognition (CCRA)

This certificate is released in accordance with the provisions of the CCRA [CC RA].

¹ The signatory countries of the SOG-IS agreements are: Austria, Finland, France, Germany, Italy, The Netherlands, Norway, Spain, Sweden and United Kingdom.

The Common Criteria Recognition Arrangement allows the recognition, by signatory countries¹, of the Common Criteria certificates. The recognition is applicable up to the assurance components of CC EAL2 level and also to ALC_FLR family. The certificates that are recognized in the agreement scope are released with the following marking:



¹ The signatory countries of the CCRA arrangement are: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, the Republic of Korea, Malaysia, Netherlands, New-Zealand, Norway, Pakistan, Singapore, Spain, Sweden, Turkey, the United Kingdom and the United States of America.

Class	Family	Component by assurance level							Assi	rance level assigned to
		EAL EAL EAL EAL EAL EAL		EAL	the product					
		EAL 1	EAL 2	EAL 3	EAL 4	EAL 5	EAL 6	EAL 7	EAL 5+	Name of the component
	ADV_ARC		1	1	1	1	1	1	1	Security architecture description
	ADV_FSP	1	2	3	4	5	5	6	5	Complete semi-formal functional specification with additional error information
ADV Development	ADV_IMP				1	1	2	2	1	Implementation representation of the TSF
Development	ADV_INT					2	3	3	2	Well-structured internals
	ADV_SPM						1	1		
	ADV_TDS		1	2	3	4	5	6	4	Semiformal modular design
AGD	AGD_OPE	1	1	1	1	1	1	1	1	Operational user guidance
User guides	AGD_PRE	1	1	1	1	1	1	1	1	Preparative procedures
	ALC_CMC	1	2	3	4	4	5	5	4	Production support, acceptance procedures and automation
	ALC_CMS	1	2	3	4	5	5	5	5	Development tools CM coverage
ALC	ALC_DEL		1	1	1	1	1	1	1	Delivery procedures
Life cycle	ALC_DVS			1	1	1	2	2	2	Sufficiency of security measures
support	ALC_FLR									
	ALC_LCD			1	1	1	1	2	1	Developer defined life-cycle model
	ALC_TAT				1	2	3	3	2	Compliance with implementation standards
	ASE_CCL	1	1	1	1	1	1	1	1	Conformance claims
	ASE_ECD	1	1	1	1	1	1	1	1	Extended components definition
ASE	ASE_INT	1	1	1	1	1	1	1	1	ST introduction
Evaluation of the	ASE_OBJ	1	2	2	2	2	2	2	2	Security objectives
security target	ASE_REQ	1	2	2	2	2	2	2	2	Derived security requirements
	ASE_SPD		1	1	1	1	1	1	1	Security problem definition
	ASE_TSS	1	1	1	1	1	1	1	1	TOE summary specification
	ATE_COV		1	2	2	2	3	3	2	Analysis of coverage
ATE	ATE_DPT			1	1	3	3	4	3	Testing: modular design
Tests	ATE_FUN		1	1	1	1	2	2	1	Functional testing
	ATE_IND	1	2	2	2	2	2	3	2	Independent testing: sample
AVA Vulnerability assessment	AVA_VAN	1	2	2	3	4	5	5	5	Advanced methodical vulnerability analysis

Annex 2. Evaluated product references

[ST]	 Reference Security target for the evaluation: MINOS – ID-One eIDL in EAC configuration with BAP and AA on P60x080 PVC/PVG Security Target, version 2, reference: 110 7890, 2nd March 2016, Oberthur Technologies. For publication needs, the following security target has been provided and validated for the present evaluation : ID-One eIDL v1.0 in EAC configuration with BAP and AA on NXP P60x080 PVC/PVG – Public Security Target, version 1, reference: 110 8164, Oberthur Technologies.
[ETR]	Evaluation Technical Report : - Evaluation Technical Report – MINOS MRTD, version 2.1, reference: LETI.CESTI.MIN.RTE.001, 6th July 2016, LETI.
[CONF]	 Product configuration list: MINOS ID-One ePass Full EACv2 MRTD and ID-One eIDL Configuration List, version 3, 4th July 2016, reference 110 7903, Oberthur Technologies.
[GUIDES]	 Product installation guide : MINOS – MRTD FULL EAC V2 – Guidance Document – PREparative procedures, version 11, 2nd March 2016, reference : 110 7111, Oberthur Technologies ; MINOS – ID-One eIDL v1.0 in EAC configuration with BAP and AA – Guidance Document – PREparative procedures, version 2, reference : 110 7931, on the 16th March 2016, Oberthur Technologies. Product user Guide : MINOS – MRTD full EAC v2 – Guidance Document – OPErational user guidance, version 3, on the 24th June 2015, reference 110 7565, Oberthur Technologies.
[BSI-PP- 0035-2007]	Security IC Platform Protection Profile, version 1.0, august 2007. Certified by BSI (Bundesamt für Sicherheit in der Informationstechnik) under the reference BSI-PP-0035-2007.
[BSI-DSZ- CC-0837- V2-2014]	NXP Secure Smart Card Controller P60x080/052/040PVC(Y/Z/A)PVG with IC Dedicated Software. <i>Certified by BSI on the 24th October 2014 under the reference BSI-DSZ-CC-0837-V2-2014.</i>

Annex 3. Certification references

	r 2002-535, 18th April 2002, modified related to the security evaluations ons for information technology products and systems.
[CER/P/01]	Procedure CER/P/01 - Certification of the security provided by Information Technology products and systems, ANSSI.
[CC]	 Common Criteria for Information Technology Security Evaluation : Part 1: Introduction and general model, September 2012, version 3.1, revision 4, reference CCMB-2012- 09-001; Part 2: Security functional components, September 2012, version 3.1, revision 4, reference CCMB-2012- 09-002; Part 3: Security assurance components, September 2012, version 3.1, revision 4, reference CCMB-2012- 09-003.
[CEM]	Common Methodology for Information Technology Security Evaluation : Evaluation Methodology, September 2012, version 3.1, revision 4, reference CCMB-2012- 09-004.
[JIWG IC] *	Mandatory Technical Document - The Application of CC to Integrated Circuits, version 3.0, February 2009.
[JIWG AP] *	Mandatory Technical Document - Application of attack potential to smartcards, version 2.9, January 2013.
[COMP] *	Mandatory Technical Document – Composite product evaluation for Smart Cards and similar devices, version 1.2, January 2012.
[CC RA]	Arrangement on the Recognition of Common Criteria Certificates in the field of Information Technology Security, 2 nd July 2014.
[SOG-IS]	« Mutual Recognition Agreement of Information Technology Security Evaluation Certificates », version 3.0, 8 th January 2010, Management Committee.
[REF]	Cryptographic mechanisms – Rules and recommendations regarding the choice and sizing of cryptographic mechanisms, version 2.03 dated 21st February 2014 appended to the General Security Standard (RGS_B1), refer to: www.ssi.gouv.fr.

Cryptographic keys management – Rules and recommendations concerning the management of keys used in cryptographic mechanisms, version 2.00 dated 8th June 2012, appended to the General Security Standard (RGS_B2), refer to www.ssi.gouv.fr.

Authentication – Rules and recommendations concerning the standard robustness level authentication mechanisms, version 1.0 dated 13th January 2010, appended to the General Security Standard (RGS_B3), refer to www.ssi.gouv.fr.

*SOG-IS document; in the scope of the CCRA recognition agreement, the equivalent CCRA supporting document applies.