

PREMIER MINISTRE

Secrétariat général de la défense et de la sécurité nationale Agence nationale de la sécurité des systèmes d'information

Certification Report ANSSI-CC-2016/41

ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on P60x144PVA/PVE components

Paris, 23 june 2016

Courtesy Translation



Warning

This report is designed to provide sponsors with a document enabling them to assess the security level of a product under the conditions of use and operation defined in this report for the evaluated version. It is also designed to provide the potential purchaser of the product with the conditions under which he may operate or use the product so as to meet the conditions of use for which the product has been evaluated and certified; that is why this certification report must be read alongside the evaluated user and administration guidance, as well as with the product security target, which presents threats, environmental assumptions and the supposed conditions of use so that the user can judge for himself whether the product meets his needs in terms of security objectives.

Certification does not, however, constitute a recommendation product from ANSSI (French Network and Information Security Agency), and does not guarantee that the certified product is totally free of all exploitable vulnerabilities.

Any correspondence about this report has to be addressed to:

Secrétariat général de la défense et de la sécurité nationale Agence nationale de la sécurité des systèmes d'information Centre de certification 51, boulevard de la Tour Maubourg 75700 PARIS cedex 07 SP France

certification.anssi@ssi.gouv.fr

Reproduction of this document without any change or cut is authorised.

Page 2 out 17 ANSSI-CC-CER-F-07EN.008

Certification report reference

ANSSI-CC-2016/41

Product name

ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on P60x144PVA/PVE components

Product reference

SAAAAR 080031 : ePass V3 Full EACv2 on NXP SAAAAR 082456 : Code r6.0 Generic

SAAAAR 082844 : Optional Code r4.0 Digital Blurred Image

Protection profile conformity

BSI-CC-PP-0055, [PP BAC], version 1.10

Machine Readable Travel Document with ICAO application, Basic Access Control

Evaluation criteria and version

Common Criteria version 3.1 revision 4

Evaluation level

EAL 4 augmented

ADV_FSP.5, ADV_INT.2, ADV_TDS.4, ALC_CMS.5, ALC_DVS.2, ALC_TAT.2, ATE_DPT.3

Developers

Oberthur Technologies

NXP Semiconductors

420 rue d'Estienne d'Orves CS 40008 Box 54 02 40, D-22502 Hamburg, Allemagne

92705 Colombes, France

Sponsor

Oberthur Technologies

420 rue d'Estienne d'Orves CS 40008

92705 Colombes, France

Evaluation facility

CEA - LETI

17 rue des martyrs, 38054 Grenoble Cedex 9, France

Recognition arrangements

CCRA

SOG-IS





The product is recognised at EAL2 level.

ANSSI-CC-CER-F-07EN.008 Page 3 out 17

Introduction

The Certification

Security certification for information technology products and systems is governed by decree number 2002-535 dated April, 18th 2002, modified. This decree stipulates that:

- The French Network and Information Security Agency draws up **certification reports**. These reports indicate the features of the proposed security targets. They may include any warnings that the authors feel the need to mention for security reasons. They may or may not be transmitted to third parties or made public, as the sponsors desire (article 7).
- The **certificates** issued by the Prime Minister certify that the copies of the products or systems submitted for evaluation fulfil the specified security features. They also certify that the evaluations have been carried out in compliance with applicable rules and standards, with the required degrees of skill and impartiality (article 8).

The procedures are available on the Internet site www.ssi.gouv.fr.

Page 4 out 17 ANSSI-CC-CER-F-07EN.008



Contents

1. THE	PRODUCT	6
	Product identification Security services Architecture Life cycle	6 6 7 7
	EVALUATION	
2.2. 1 2.3. C	EVALUATION REFERENTIAL EVALUATION WORK CRYPTOGRAPHIC MECHANISMS ROBUSTNESS ANALYSIS ACCORDING TO THE ANSSI'S CAL STANDARDS RANDOM NUMBER GENERATOR ANALYSIS	9 9
3.1. 3.2.	CONCLUSION	11 11
3.3.1. 3.3.2. ANNEX 1.	International common criteria recognition (CCRA)	11
ANNEX 1. ANNEX 2.		
ANNEX 3	CERTIFICATION REFERENCES	16

1. The product

1.1. Presentation of the product

The evaluated product is the smart card « ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on P60x144PVA/PVE components », which can be in contact or contactless mode. This product is developed by *OBERTHUR TECHNOLOGIES* on a component manufactured by *NXP SEMICONDUCTORS*.

This product implements electronic travel document functionalities based on the International Civil Aviation Organization and the European Civil Aviation Conference specifications and requirements. This product is used to verify a travel document's authenticity and its holder identification during a border control process through an inspection system.

The evaluation target is composed of the ID-One ePass Full EAC v2 MRTD application, in BAC (*Basic Access Control*) configuration with AA (*Active Authentication*) and CA (*Chip Authentication*) which carries out the electronic passport functions.

This micro-controller and its embedded software are intended to be inserted into the cover page of standard passports. They can be integrated into modules or *inlays*. The final product can be a passport, plastic card, etc.

1.2. Evaluated product description

1.2.1. Introduction

The security target [ST] defines the evaluated product, its evaluated security functionalities and its operational environment.

This security target is fully compliant with the protection profile [PP BAC].

1.2.2. Product identification

The configuration list [CONF] identifies the product's constituent elements.

The certified version of the product can be identified by the following elements:

- Commercial name: ID-One ePass Full EAC V2;
- SAAAAR¹ code of ROM code : 080031;
- Mandatory patch code: 412E4D1EC087005B56A9A2CAC0B6558F4CAA E041D8B5A69345559B562A6F4C8E;
- Optional patch code : E339C30BC6A81162413612FE2698284FA6CD28AA5 CF5257A20B83611E58E9BEE;
- Component code (on 42 bytes): XXXXvvvvXX..XX where vvvv can take the following values:

Page 6 out 17 ANSSI-CC-CER-F-07EN.008

¹ S: code site (0 for France), AAAA: article based on 4 numbers, R: software *release* or version.

SÉCURITÉCETIFICATION

- '6A15' for P60D144PVA component;
- '6E15' for P60D144PVE component;
- '6A20' for P60C144PVA component;
- '6E20' for P60C144PVE component.

It can be decided whether or not to load the optional patch and whether or not to the *Digital Blurred Image* function.

The "SAAAAR and patch" codes can be verified using a GetData command with the DF66 tag. The component code can be verified using a GetData command with the 9F7F tag described in the [GUIDES].

1.2.3. Security services

The main security services provided by the product are:

- Integrity Protection of the cardholder's data stored in the card: issuing nations or authorities, travel document number, expiry date, name of the holder, nationality, date of birth, sex, portrait, other optional data, additional biometric reference data and other data for managing the security of the travel document;
- Access control to the cardholder's data stored in the card;
- Integrity and confidentiality protection, through the *Secure Messaging* mechanism, of the data read on the card;
- Verification of the certificates' validation chain;
- Authentication of the micro-controller using the optional « *Active Authentication and Chip Authentication* » mechanisms.

There is an optional non evaluated function of *Digital Blurred Image* which makes the photo illegible in case of a fraudulent use.

1.2.4. Architecture

The product is a closed smart card which contained the following components:

- a micro-controller P60x144PVA/PVE manufactured by *NXP Semiconductors*, in P60D144PVA, P60D144PVE, P60C144PVA or P60C144PVE configuration;
- The "BIOS" software giving access to micro-controller functionalities;
- a dedicated cryptographic library;
- the *Perso* personalization application;
- a LDS¹ application supporting EAC, PACE, PACE CAM, CA and AA mechanisms;
- The eID application;
- The *eSign* application outside of the evaluation scope;
- The *Dauth* application outside of the evaluation scope.

_

ANSSI-CC-CER-F-07EN.008 Page 7 out 17

¹Logical Data Structure.

1.2.5. Life cycle

The product's life cycle is organised as follow:

	Phase	Actor	Covered by			
Step 1	Development	OBERTHUR	ALC			
		TECHNOLOGIES				
Step 2	Development	NXP	Component			
		SEMICONDUCTORS	Certification			
Step 3	Manufacturing	NXP	Component			
		SEMICONDUCTORS	Certification			
	TOE delivery point					
Step 4	MRTD manufacturer	MRTD manufacturer	AGD_PRE			
	(Pre-perso)					
Step 5	MRTD manufacturer	MRTD manufacturer	AGD_PRE			
	(Pre-perso)					
Step 6	Personalization	Personalization agent	AGD_PRE			
Step 7	Operational use	End user	AGD_OPE			

The product has been developed on the following site:

OBERTHUR TECHNOLOGIES – Colombes site 420 rue d'Estienne d'Orves 92700 Colombes France

OBERTHUR TECHNOLOGIES -Pessac site

Parc Scientifique UNITEC 1 4 allée du Doyen Georges Brus – Porte 2 33600 Pessac France

The micro-controller is developed and manufactured by *NXP SEMICONDUCTORS*. The development and manufacturing sites for the micro-controller are detailed in the certification report under the reference [BSI-DSZ-CC-0978-2016].

The "product administrators" are the nations or authorities issuing the driving license. The "product users" are both the holders of driving license and the inspection systems during the use phase.

1.2.6. Evaluated configuration

The product is a closed card that can be personalized into different configurations. This certification report applies to the configuration including the following mechanisms:

- Basic Access Control;
- Active Authentication.

Page 8 out 17 ANSSI-CC-CER-F-07EN.008

2. The evaluation

2.1. Evaluation referential

The evaluation has been performed in compliance with the **Common Criteria version 3.1 revision 4** [CC], in accordance with the Common Evaluation Methodology defined in [CEM].

For assurance components which are not covered by the [CEM] manual, methods specific to the evaluation facility were used.

In order to meet specific features of smart cards, the [JIWG IC] and [JIWG AP] guides were applied. Thus, the AVA_VAN level was determined using the rating scale of the [JIWG AP] guide. For the record, this rating scale is more demanding than that defined by default in the standard method [CC], used for other categories of products (software products for example).

2.2. Evaluation work

The evaluation has been performed according to the composition scheme defined in the guide [COMP], in order to assess that no weakness arises from the integration of the software in the certified microcontroller.

Therefore, the results of the evaluation of the microcontroller « P60x144PVA/PVE » at EAL6 level augmented with ALC_FLR.1 and ASE_TSS.2 components, compliant with the [BSI-PP-0035-2007] protection profile, have been used. This microcontroller has been certified the 5th February 2016 under the reference [BSI-DSZ-CC-0978-2016].

The evaluation technical report [ETR], delivered to ANSSI the 18th March 2016, provides details on the work performed by the evaluation facility and assesses that all evaluation tasks are "pass".

2.3. Cryptographic mechanisms robustness analysis according to the ANSSI's technical standards

The rating of the cryptographic mechanisms robustness has been carried out according to the ANSSI [REF] technical standards.

The results obtained have been the subject of an analysis report [ANA-CRY] which leads to the following conclusions:

- The analyzed mechanisms are compliant to the ANSSI ([REF]) technical standard requirements, provided the recommendations mentioned in the guides (refer to [GUIDES]) are followed;
- The Hash function SHA-1 must not be used for signature applications.

As part of the reinforced qualification process, an expertise of cryptography's implementation was realized by the ITSEF. These results were taken into account in the independent vulnerability analysis realized by the evaluator and have not allowed to highlight exploitable vulnerabilities for the intended target namely AVA_VAN.3 level.

ANSSI-CC-CER-F-07EN.008 Page 9 out 17

2.4. Random number generator analysis

The physical random number generator used by the final product was evaluated within the scope of the micro-controller evaluation (Refer to [BSI-DSZ-CC-0978-2016]).

In addition, as required in the ANSSI cryptographic standard ([REF]), the output of the physical random number generator is reprocessed using a cryptographic function.

The results were taken into account in the independent vulnerability analysis carried out by the evaluator and found no evidence of exploitable vulnerability for the AVA_VAN.3 level targeted.

Page 10 out 17 ANSSI-CC-CER-F-07EN.008

3. Certification

3.1. Conclusion

The evaluation was carried out according to the current rules and standards, with the required competency and impartiality of a licensed evaluation facility. All the work performed permits the release of a certificate in conformance with the decree 2002-535.

This certificate testifies that the product « ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on P60x144PVA/PVE components » submitted for evaluation fulfils the security features specified in its security target [ST] for the evaluation level EAL4 augmented by ADV_FSP.5, ADV_INT.2, ADV_TDS.4, ALC_CMS.5, ALC_DVS.2, ALC_TAT.2, ATE_DPT.3 components.

3.2. Restrictions

This certificate only applies on the product specified in chapter 1 of this certification report.

The user of the certified product shall respect the security objectives for the operational environment, as specified in the security target [ST], and shall respect the recommendations in the guidance [GUIDES].

3.3. Recognition of the certificate

3.3.1. European recognition (SOG-IS)

This certificate is released in accordance with the provisions of the SOG-IS agreement [SOG-IS]. The European Recognition Agreement made by SOG-IS in 2010 allows recognition from Signatory States of the agreement¹, of ITSEC and Common Criteria certificates. The European recognition is applicable, for smart cards and similar devices, up to ITSEC E6 High and CC EAL7 levels. The certificates that are recognized in the agreement scope are released with the following marking:



3.3.2. International common criteria recognition (CCRA)

This certificate is released in accordance with the provisions of the CCRA [CC RA].

ANSSI-CC-CER-F-07EN.008 Page 11 out 17

-

¹ The signatory countries of the SOG-IS agreements are: Austria, Finland, France, Germany, Italy, The Netherlands, Norway, Spain, Sweden and United Kingdom.

The Common Criteria Recognition Arrangement allows the recognition, by signatory countries¹, of the Common Criteria certificates. The recognition is applicable up to the assurance components of CC EAL2 level and also to ALC_FLR family. The certificates that are recognized in the agreement scope are released with the following marking:



Page 12 out 17 ANSSI-CC-CER-F-07EN.008

¹ The signatory countries of the CCRA arrangement are: Australia, Austria, Canada, Czech Republic, Denmark, Finland, France, Germany, Greece, Hungary, India, Israel, Italy, Japan, the Republic of Korea, Malaysia, Netherlands, New-Zealand, Norway, Pakistan, Singapore, Spain, Sweden, Turkey, the United Kingdom and the United States of America.

Annex 1. Evaluation level of the product

Class	Family	Component by assurance level						Assurance level assigned to the product		
					EAL				EAL	Name of the component
	ADV_ARC	1	1	1	1	5 1	1	7	4+ 1	Security architecture
										description Complete functional
. 5.4	ADV_FSP	1	2	3	4	5	5	6	5	specification
ADV Development	ADV_IMP				1	1	2	2	1	Implementation representation of TSF
Bevelopment	ADV_INT					2	3	3	2	Well-structured internals
	ADV_SPM						1	1		
	ADV_TDS		1	2	3	4	5	6	4	Basic modular design
AGD	AGD_OPE	1	1	1	1	1	1	1	1	Operational user guidance
User guides	AGD_PRE	1	1	1	1	1	1	1	1	Preparative procedures
	ALC_CMC	1	2	3	4	4	5	5	4	Production support, acceptance procedures and automation
	ALC_CMS	1	2	3	4	5	5	5	5	Problem tracking CM coverage
ALC	ALC_DEL		1	1	1	1	1	1	1	Delivery procedures
Life cycle support	ALC_DVS			1	1	1	2	2	2	Sufficiency of security measures
support	ALC_FLR									
	ALC_LCD			1	1	1	1	2	1	Developer defined life-cycle model
	ALC_TAT				1	2	3	3	2	Well-defined development tools
	ASE_CCL	1	1	1	1	1	1	1	1	Conformance claims
	ASE_ECD	1	1	1	1	1	1	1	1	Extended components definition
ASE	ASE_INT	1	1	1	1	1	1	1	1	ST introduction
Evaluation of the	ASE_OBJ	1	2	2	2	2	2	2	2	Security objectives
security target	ASE_REQ	1	2	2	2	2	2	2	2	Derived security requirements
	ASE_SPD		1	1	1	1	1	1	1	Security problem definition
	ASE_TSS	1	1	1	1	1	1	1	1	TOE summary specification
	ATE_COV		1	2	2	2	3	3	2	Analysis of coverage
ATE	ATE_DPT			1	1	3	3	4	3	Testing: basic design
Tests	ATE_FUN		1	1	1	1	2	2	1	Functional testing
	ATE_IND	1	2	2	2	2	2	3	2	Independent testing: sample
AVA Vulnerability assessment	AVA_VAN	1	2	2	3	4	5	5	3	Focused vulnerability analysis

ANSSI-CC-CER-F-07EN.008 Page 13 out 17

Annex 2. Evaluated product references

[ST]	Reference Security target for the evaluation: - MINOS – ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on NXP P60x144 PVA/PVE – Security Target, version 2, reference : 110 7885, 2 nd March 2016, Oberthur Technologies.			
	For publication needs, the following security target has been provided and validated for the present evaluation: - ID-One ePass Full EAC v2 MRTD in BAC configuration with AA and CA on NXP P60x144 PVA/PVE – Public Security Target, version 2, reference: 110 7963, Oberthur Technologies.			
[ETR]	Evaluation Technical Report : - Evaluation Technical Report – MINOS MRTD, version 2.0, reference LETI.CESTI.MIN.RTE.001, 18th March 2016, LETI.			
[ANA-CRY]	MINOS – Cryptographic sizing mechanism MRTD, version 2.0, reference: LETI.CESTI.MIN.RT.033, 18th March 2016, LETI.			
[CONF]	Product configuration list: - MINOS ID-One ePass Full EACv2 MRTD and ID-One eIDL Configuration List, version 2, 16 th March 2016, reference 110 7903, Oberthur Technologies.			
[GUIDES]	Product installation guide: - MINOS – MRTD FULL EAC V2 – Guidance Document – PREparative procedures, version 11, 2 nd March 2016, reference: 110 7111, Oberthur Technologies; - MINOS – ID-One ePass Full EACv2 MRTD in BAC configuration with AA – Guidance Document – PREparative procedures, version 2, reference: 110 7926, 16 th March 2016, Oberthur Technologies.			
	Product user Guide: - MINOS – MRTD full EAC v2 – Guidance Document – OPErational user guidance, version 3, 24th june 2015, reference 110 7565, Oberthur Technologies.			
[PP BAC]	Protection Profile - Machine Readable Travel Document with ICAO Application, Extended Access Control, version 1.10, 25th March 2009. Certified by BSI (Bundesamt für Sicherheit in der Informationstechnik) on the 7th May 2009 under the reference BSI-CC-PP-0055-2009.			
[BSI-PP- 0035-2007]	Security IC Platform Protection Profile, version 1.0, august 2007. Certified by BSI (Bundesamt für Sicherheit in der Informationstechnik) under the reference BSI-PP-0035-2007.			

Page 14 out 17 ANSSI-CC-CER-F-07EN.008

[BSI-DSZ-	NXP	Secure	Smart	Card	Controller
CC-0978-	P60x144	/080yVA/yVA(Y/	B/X)/yVE with	IC Dedicated S	Software.
2016]	Certified	by BSI on the 5	th February 2	016 under the	reference BSI-
	DSZ-CC	-0978-2016.			

ANSSI-CC-CER-F-07EN.008 Page 15 out 17

Annex 3. Certification references

Decree number 2002-535, 18th April 2002, modified related to the security evaluations and certifications for information technology products and systems.				
[CER/P/01]	Procedure CER/P/01 - Certification of the security provided by Information Technology products and systems, ANSSI.			
[CC]	Common Criteria for Information Technology Security Evaluation: Part 1: Introduction and general model, September 2012, version 3.1, revision 4, reference CCMB-2012-09-001; Part 2: Security functional components, September 2012, version 3.1, revision 4, reference CCMB-2012-09-002; Part 3: Security assurance components, September 2012, version 3.1, revision 4, reference CCMB-2012-09-003.			
[CEM]	Common Methodology for Information Technology Security Evaluation : Evaluation Methodology, September 2012, version 3.1, revision 4, reference CCMB-2012-09-004.			
[JIWG IC] *	Mandatory Technical Document - The Application of CC to Integrated Circuits, version 3.0, February 2009.			
[JIWG AP] *	Mandatory Technical Document - Application of attack potential to smartcards, version 2.9, January 2013.			
[COMP] *	Mandatory Technical Document – Composite product evaluation for Smart Cards and similar devices, version 1.2, January 2012.			
[CC RA]	Arrangement on the Recognition of Common Criteria Certificates in the field of Information Technology Security, 2 nd July 2014.			
[SOG-IS]	« Mutual Recognition Agreement of Information Technology Security Evaluation Certificates », version 3.0, 8 th January 2010, Management Committee.			
[REF]	Cryptographic mechanisms – Rules and recommendations regarding the choice and sizing of cryptographic mechanisms, version 2.03 dated 21st February 2014 appended to the General Security Standard (RGS_B1), refer to: www.ssi.gouv.fr.			

Page 16 out 17 ANSSI-CC-CER-F-07EN.008



Cryptographic keys management – Rules and recommendations concerning the management of keys used in cryptographic mechanisms, version 2.00 dated 8th June 2012, appended to the General Security Standard (RGS_B2), refer to www.ssi.gouv.fr.

Authentication – Rules and recommendations concerning the standard robustness level authentication mechanisms, version 1.0 dated 13th January 2010, appended to the General Security Standard (RGS_B3), refer to www.ssi.gouv.fr.

*SOG-IS document; in the scope of the CCRA recognition agreement, the equivalent CCRA supporting document applies.

ANSSI-CC-CER-F-07EN.008 Page 17 out 17